

GAS CHROMATOGRAPHY SYSTEM

GC-1100



GC-1100

Product Description:

The GC-1100 Series is Phylo's new generation of gas chromatographs. As compared with the GC-1000A Series, a number of technical improvements have resulted in better performance and greater automation. Up to ten gas paths can be controlled using EPC flow or pressure control, including the carrier gas, ignition gas, auxiliary gas, split flow and makeup gas, among others. Detector and column.

Technical feature:

• Self-diagnostic function:

(1) Core tests; (2) Automatic tests; (3) Extended tests; (4) Basic tests;
Monitor the status of GC continuously. Once finding faults, it will display the information, show the wrong zone and the settling method.

• Self-protective function:

(1) Overrun temperature protection; (2) Short circuit hint; (3) TCD filament protection; (4) FID flameout hint;
(5) PFD exposed-light protection; (6) Keyboard locked function utilizing password; more kinds of protect function ensured GC's normally running.

• Simple operation, powerful automation:

(1) All parameters can be entered through keyboard with prompt function;
(2) Storing 4 complete chromatography analysis methods which can be activated automatically;
(3) Can be connected with Autosampler;
(4) Parameters can be modified instantly while the GC is running;
(5) Chromatography analysis method can be activated for 99 times repeatedly at one time. It's especially suitable for in nobody guarding situation. kinds of protect function ensured GC's normally running.

• Simple operation, powerful automation:

(1) All parameters can be entered through keyboard with prompt function;
(2) Storing 4 complete chromatography analysis methods which can be activated automatically;
(3) Can be connected with Autosampler;
(4) Parameters can be modified instantly while the GC is running;
(5) Chromatography analysis method can be activated for 99 times repeatedly at one time. It's especially suitable for in nobody guarding situation.

• More choices of injectors:

(1) On-Column Injector for Packed Column; (2) Flash Vaporization Injector for Packed Column
(3) Automatic or manual gas inject valve; (4) Headspace sampler; (5) Thermal desorption system
(6) Split/Splitless Capillary Injector; Three Injectors or two Split/Splitless Capillary Injectors can be fixed on GC.

• More choices of detectors:

(1) TCD; (2) FID; (3) ECD; (4) FPD; (5) TSD
Maximum of two TCD installed or three different kind of detectors.

- **Reactor:** (1) Internal; (2) External

- **Time programming of Detectors:**

Each of detectors has 5-ramp programmable time control, output-signal, attenuation range, and polarity can be changed automatically.

- **Time programming of external events:**

Provide 4 external events with 20-ramp programmable time control; the optional GC relays may be used to automate valves, to operate split/splitless capillary injectors, or drive auxiliary functions, or switch signal between detectors A and detector B during a run.

- **According to user's request**, many kind of special-purpose GC can be provided, realizing multidimensional methods of analysis.

Technical Specifications:

- **Column oven:**

- Operating temperature range: ambient temperature to 420°C;
- Owning dual opening-door at the back of the column oven;
- Cooling time: 250°C to 50°C in 5 min;
- Programmable oven with 4-ramp temperature control;
- Temperature programming rate: 0.1~50°C/min

- **Injector system:**

- Operating temperature range: ambient temperature to 420°C

- **Thermal conductivity detector-TCD:**

- Maximum temperature: 420°C
- Linear range: 10^5
- Current range: 50 to 400mA
- Filament protection: If He or H₂ carrier gas flow in the detector cell is off for 4 minutes, filament power automatically shuts off.

- **Flame ionization detector-FID:**

- Maximum temperature: 420°C
- Minimum directivity: $\leq 1.3 \times 10^{-12}$ g/s (n-C₁₆)
- Linear range: 10^7
- Flameout hint: monitoring the status of GC continuously, after being turned on.

- **Electron capture detector-ECD:**

- Maximum temperature: 420°C
- Minimum detectivity: ≤ 0.1 pg/mL (γ -666)
- Linear range: 10^4
- Emission source: ¹¹³Cd/⁶³Ni

- **Flame photometric detector-FPD:**

- Maximum temperature: 420°C
- Minimum detectivity: [P] $\leq 1 \times 10^{-12}$ g/s (tributyl phosphate), [S] $\leq 1 \times 10^{-10}$ g/s (p-methylsulfurphosphorous)
- Linear range: [P]: 10^5 [S]: 10^3
- Two air-hydrogen flames: For large volume injection or trace sample injection analyses;
- Single air-hydrogen flame: sulfur sensitivity can be increased;
- Direct output: for phosphorus or sulfur analyses;
- Square-root output: for sulfur analyses;
- Exposed-light protection: when exposed-light current $\geq 12\mu A$, high voltage will be cut off automatically.

- **Nitrogen-phosphorus detector-TSD:**

- Maximum temperature: 420°C
- Minimum detectivity: [N] $\leq 1 \times 10^{-13}$ g/s (azobenzene), [P] $\leq 5 \times 10^{-14}$ g/s (malathion)
- Linear range: [N]: 10^5 [P]: 10^4

PHYLO
FOR TECHNOLOGY

P.iva 03176751208

VIA EDOARDO FERRAVILLA, 19

40127-BOLOGNA

ITALY